

WHAT IS CLAIMED IS:

1. A seat belt guiding auxiliary device comprising:

a seat base positioned under buttocks of a person sitting on a bench seat in a car;

5 a pair of loop parts rising upward from forward both side edges of said seat base along both sides of the buttocks of the sitting person, and passing a waist belt part of a car seat belt; and

a pair of slanted connecting members connecting an upper end of said each loop part to each of backward side edges of the seat base.

10 2. The seat belt guiding auxiliary device according to claim 1, wherein the seat belt guiding auxiliary device has a configuration of a seat mat laid under the buttocks of the sitting person.

3. The seat belt guiding auxiliary device according to claim 1, wherein the seat belt guiding auxiliary device has a configuration of a juvenile seat
15 positioned on a car bench seat to increase a seated height of the sitting person.

4. The seat belt guiding auxiliary device according to claim 1, wherein said loop part comprises an extension turn-round portion continuously extending from said seat base and being folded back to the outside.

20 5. The seat belt guiding auxiliary device according to claim 4, wherein said seat base and said extension turn-round portion are sewed members formed continuously.

6. The seat belt guiding auxiliary device according to claim 4, wherein said loop part comprises connecting means for detachably connecting the
25 end of said extension turn-round portion to a back surface of said seat base.

7. The seat belt guiding auxiliary device according to claim 6, wherein said connecting means comprises;

an extension belt extending from the end of said extension turn-round portion;

30 a base belt extending from the back surface of said seat base; and
a buckle detachably connecting said extension belt and said base belt.

8. The seat belt guiding auxiliary device according to claim 7, wherein a length of said extension belt can be adjusted.

35 9. The seat belt guiding auxiliary device according to claim 7, wherein said base belt extends over the whole length of the back surface of said seat

base in the width direction thereof.

10. The seat belt guiding auxiliary device according to claim 1, wherein said each slanted connecting member continuously rises and extends from the side edge of said seat base.

5 11. The seat belt guiding auxiliary device according to claim 4, wherein said seat base, said each slanted connecting member, and said each extension turn-round portion are sewed members formed continuously.

10 12. The seat belt guiding auxiliary device according to claim 1, comprising a back support cushion rising from a backward edge of said seat base to support the back of the sitting person from behind.

13. The seat belt guiding auxiliary device according to claim 12, comprising means for detachably connecting said back support cushion to the backward edge of said seat base.

15 14. The seat belt guiding auxiliary device according to claim 12, wherein said seat base comprises a flexible backward extension portion extending backward or upward from the backward edge, and said back support cushion is connected to said backward extension portion.

15. The seat belt guiding auxiliary device according to claim 1, comprising a seat base fixing member fixing said seat base to a car bench sheet.

20 16. The seat belt guiding auxiliary device according to claim 1, wherein said seat base is a seated portion of a seat originally provided in a car.

17. The juvenile car seat comprising:

a seat base positioned on a car bench seat and having a predetermined height; and

25 a pair of loop parts rising upward from forward both side edges of said seat base along both sides of buttocks of a sitting person, and passing a waist belt part of a car seat belt.

18. The juvenile car seat according to claim 17, wherein said loop part is formed of a flexible material.

30 19. The juvenile car seat according to claim 17, comprising a slanted connecting member connecting an upper end of said each loop part to a backward side edge of said seat base.

20. The juvenile car seat according to claim 17, comprising a backrest wall rising and extending upward from the backward edge of said seat base.